



Pimasa





why choose Pimasa?

At Pinturas Pimasa we produce acrylic paints and coatings for professionals, distinguished by their functionality, ease of use, quality and durability.

Our first steps in the sector date back to 1958 with the development of vegetable glue, copal varnish, tempera paste, and putty in a same small 300 square meter nave on the outskirts of Albacete. In 1970 we began to produce acrylic paints and coatings.

In 1985, due to product growth and an increase in scales, we established Pinturas Pimasa, S.L. by moving to a new factory located in the Campollano Industrial Park in Albacete.

In 2016 we expanded and modernised our factory, aimed at growth of our production capacity, research, product and process development and a commitment to the environment.

At Pinturas Pimasa we assist our customers with the very best service and solutions.

***Our fast service
and direct
contact with
customers
and suppliers
sets us apart.***

***Our products are
distinguished
by offering the
best quality-cost
relationship
on the market.***

interior matte paint



**matte
low cost**

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of interior surfaces.

FEATURES

Excellent adhesion on cement, concrete, brick and other construction materials.

Stable white, not yellow.

Well-balanced whiteness, for protection of indoor walls.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 6-12 m²/l

SIZE: 4-15 l

interior matte paint



matte 2001

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of interior surfaces.

FEATURES

Excellent adhesion on cement, concrete, brick and other construction materials. Breathable.

Stable white, not yellow.

Well-balanced whiteness, for protection of indoor walls.

Good resistance to scrubbing.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 6-12 m²/l

SIZE: 4-15 l

interior matte paint



matte interior

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of interior surfaces.

FEATURES

Excellent adhesion on cement, concrete, brick and other construction materials. Breathable.

Stable white, not yellow.

Well-balanced whiteness, for protection of indoor walls.

Permissible wet scrub resistance.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 6-10 m²/l

SIZE: 4-15 l

interior matte paint



**one coat
colors**

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of interior surfaces.

FEATURES

Great covering power.

Colors as available.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Well-balanced in covering and washability for protection of indoor walls.

Good washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: One coat colors chart

RECOAT TIME: 2-4 hours

COVERAGE: 8-10 m²/l

SIZE: 4-15 l

discover our colors

ONE COAT INTERIOR COLORS



CREAM




VANILLA



BEIGE




WENGUE



SAND YELLOW



ALBERO



SALMON



PEACH



TANGERINE




ORANGE



PALE PINK



CHERRY



FLAMING RED



PLUM



MAUVE



PETUNIA FUCHSIA



PISTACHIO



DAYDREAM GREEN



GREY



SKY BLUE



CALM BLUE

interior and exterior matte paint



**matte
2002**

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of interior surfaces.

FEATURES

Good covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Stable white, not yellow.

Resistance to wet scrub above 2,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor walls and permissible for exteriors.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 8-12 m²/l

SIZE: 4-15 l

interior and exterior matte paint



matte 1900 mould-resistant

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness, as well as mould-resistance due to special composition and additive.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Good covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.
Breathable.

Completely waterproof and UV-resistant.

Forms a highly mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 4,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 8-12 m²/l

SIZE: 4-15 l

interior and exterior matte paint



pimacril

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Great covering power.

Excellent adhesion on cement, concrete, brick and other construction materials. Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 4,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior matte paint



albacril

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Great covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 4,500 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 8-12 m²/l

SIZE: 4-15 l

interior and exterior matte paint



*high
covering*

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Great covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 5,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior matte paint



pimalux

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Great covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 5,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior matte paint



pimalux *mould-resistant*

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness, as well as mould-resistance due to special composition and additive.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Great covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a highly mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 5,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior matte paint



decorcril 2000

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Excellent covering power.

Excellent adhesion on cement, concrete, brick and other construction materials. Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 6,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 10-12 m²/l

SIZE: 4-15 l

interior and exterior matte paint



**super
5000**

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Excellent covering power.

Maximum whiteness.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 6,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior matte paint



**matte
silk**

DESCRIPTION

Semi-matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Excellent covering power.

Silky finish.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 6,000 cycles.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Semi-Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 10-12 m²/l

SIZE: 4-15 l

interior and exterior satin paint



1000-HU

DESCRIPTION

High-quality satin acrylic paint based on copolymer resins in watery dispersion and high-resistance and stable pigments that provide waterproof, durable, washable and opaque finishes.

It offers a nice decorative look with satin effect.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Good covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.

Weather-proof and UV-resistant.

Stable white, not yellow.

Resistance to wet scrub above 10,000 cycles.

Well-balanced whiteness, covering and washability, with adequate time for retouching.

Easy application.

FINISH: Satin

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior satin paint



1000-MUX

DESCRIPTION

High-quality satin acrylic paint based on copolymer resins in watery dispersion and high-resistance and stable pigments that provide waterproof, durable, washable and opaque finishes.

It offers a nice decorative look with satin effect.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Very good covering power.

Excellent adhesion on cement, concrete, brick and other construction materials.

Weather-proof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 10,000 cycles.

Well-balanced whiteness, covering and washability, with adequate time for retouching.

Excellent washability.

Easy application.

FINISH: Satin

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior satin paint



satilux

DESCRIPTION

High-quality satin acrylic paint based on copolymer resins in watery dispersion and high-resistance and stable pigments that provide waterproof, durable, washable and opaque finishes.

It offers a nice decorative look with satin effect.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

High-gloss acrylic paint.

Excellent covering power.

Completely waterproof.

Excellent adhesion on cement, concrete, brick and other construction materials.

Weather-proof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 10,000 cycles.

Well-balanced whiteness, covering and washability, with adequate time for retouching.

Excellent washability.

Easy application.

FINISH: Satin

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

interior and exterior satin paint



*satin
extra*

DESCRIPTION

High-quality satin acrylic paint based on copolymer resins in watery dispersion and high-resistance and stable pigments that provide waterproof, durable, washable and opaque finishes.

It offers a nice decorative look with satin effect.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

High-gloss acrylic paint.

Excellent covering power.

Completely waterproof.

Excellent adhesion on cement, concrete, brick and other construction materials.

Weather-proof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 10,000 cycles.

Well-balanced whiteness, covering and washability, with adequate time for retouching.

Excellent washability.

Easy application.

FINISH: Satin

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

facades paint



R-520

DESCRIPTION

Smooth matte coating based on acrylic resins in watery dispersion and high-strength, quality and light fast pigments.

Ideal for decoration and protection of both interior and exterior surfaces.

FEATURES

Good covering power.

Maximum whiteness.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Stable white, not yellow.

Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.

Excellent washability.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2-4 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

facades paint



revescril

DESCRIPTION

Smooth matte coating based on high-strength acrylic resins with weather-proof and light fast ingredients.

Ideal for decoration and long-term protection for all kinds of facades.

FEATURES

Great covering power.

Maximum whiteness.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Sufficiently permeable to water vapour to prevent internal condensation.

Self-cleaning.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

facades paint



d'okacril *mould-resistant*

DESCRIPTION

Smooth matte coating based on high-strength acrylic resins with weather-proof and light fast ingredients, as well as mould-resistance due to special composition and additive.

Ideal for decoration and long-term protection for all kinds of facades.

FEATURES

Great covering power.

Maximum whiteness.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a highly mould-resistant film.

Stable white, not yellow.

Sufficiently permeable to water vapour to prevent internal condensation.

Self-cleaning.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

facades paint



decotex

DESCRIPTION

Smooth matte coating based on high-strength acrylic resins with weather-proof and light fast ingredients.

Ideal for decoration and long-term protection for all kinds of facades.

FEATURES

Excellent covering power.

Maximum whiteness.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Forms a mould-resistant film.

Stable white, not yellow.

Resistance to wet scrub above 15,000 cycles.

Wide range of resistance, for both climatic weather variables and different bracket protection conditions.

Completely smooth, without frosted feel.

Sufficiently permeable to water vapour to prevent internal condensation.

Self-cleaning.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 2 hours

COVERAGE: 9-13 m²/l

SIZE: 4-15 l

facades paint



decotex colors

DESCRIPTION

Smooth matte coating based on high-strength acrylic resins with weather-proof and light fast ingredients.

Ideal for decoration and long-term protection for all kinds of facades.

FEATURES

Excellent covering power.

Colors as available.

Excellent adhesion on cement, concrete, brick and other construction materials.

Breathable.

Completely waterproof and UV-resistant.

Completely smooth, without frosted feel.

Sufficiently permeable to water vapour to prevent internal condensation.

Self-cleaning.

Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: Decotex color chart


RECOAT TIME: 2 hours

COVERAGE: 10-12 m²/l


SIZE: 4-15 l

discover our colors

DECOTEX FACADES COLORS



DARK SALMON



ALBERO



PALE GREY



SALMON



DARK BEIGE



DARK GREY



LEATHER




STONE SALMON



CINNAMON



ATLAS



SANDSTONE



DUNE



IVORY



CLAY



ALMOND



PALE BEIGE




MOSS GREEN



DARK BLUE



YELLOW



RUST RED

facades paint



pimaelast

DESCRIPTION

Semi-satin waterproof elastic coating based on acrylic copolymers in emulsion with weather-proof and light fast ingredients.

Ideal for decoration and protection of infiltrations caused by rain for all types of facades.

FEATURES

Great covering power.

Maximum whiteness.

Very high tensile strength, while still flexible, covers micro-cracks caused by contraction and expansion.

Excellent adhesion on cement, concrete, brick and other construction materials.

Stable white, not yellow.

Sufficiently permeable to water vapour to prevent internal condensation.

Self-cleaning.

Easy application.

FINISH: Semi-satin

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 6 hours

COVERAGE: 3,5-4 m²/l

SIZE: 4-15 l

facades paint



pimaelast *mould-resistant*

DESCRIPTION

Semi-satin waterproof elastic coating based on acrylic copolymers in emulsion with weather-proof and light fast ingredients, as well as mould-resistance due to special composition and additive.

Ideal for decoration and protection of infiltrations caused by rain for all types of facades.

FEATURES

Great covering power.

Maximum whiteness.

Very high tensile strength, while still flexible, covers micro-cracks caused by contraction and expansion.

Excellent adhesion on cement, concrete, brick and other construction materials.

Forms a highly mould-resistant film.

Stable white, not yellow.

Sufficiently permeable to water vapour to prevent internal condensation.

Self-cleaning.

Easy application.

FINISH: Semi-satin

DRY TIME: 30 minutes

COLOR: White

RECOAT TIME: 6 hours

COVERAGE: 3,5-4 m²/l

SIZE: 4-15 l

waterproof paint



red

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 450% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Tensile strength of 25 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 1-2 hours

COLOR: Red

RECOAT TIME: 12-24 hours

COVERAGE: 1,5-2 m²/l

SIZE: 4-15 l

waterproof paint



white

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 450% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Tensile strength of 25 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 1-2 hours

COLOR: White

RECOAT TIME: 12-24 hours

COVERAGE: 1,5-2 m²/l

SIZE: 4-15 l

waterproof paint



grey

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 450% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Tensile strength of 25 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 1-2 hours

COLOR: Grey

RECOAT TIME: 12-24 hours

COVERAGE: 1,5-2 m²/l

SIZE: 4-15 l

waterproof paint



**red
heavy coat**

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 550% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Tensile strength of 30 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 1-2 hours

COLOR: Red

RECOAT TIME: 12-24 hours

COVERAGE: 1,5-2 m²/l

SIZE: 4-15 l

waterproof paint



*white
heavy coat*

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 550% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Tensile strength of 30 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 1-2 hours

COLOR: White

RECOAT TIME: 12-24 hours

COVERAGE: 1,5-2 m²/l

SIZE: 4-15 l

waterproof paint



**grey
heavy coat**

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 550% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Tensile strength of 30 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 1-2 hours

COLOR: Grey

RECOAT TIME: 12-24 hours

COVERAGE: 1,5-2 m²/l

SIZE: 4-15 l

waterproof paint



DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 550% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Tensile strength of 30 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

**transparent
heavy coat**

FINISH: Satin

DRY TIME: 1-2 hours

COLOR: Transparent

RECOAT TIME: 12-24 hours

COVERAGE: 1,5-2 m²/l

SIZE: 4-15 l

waterproof paint



*red
with fiber*

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 550% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Greater tensile strength by the incorporation of fiber.
Tensile strength of 35 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 4-8 hours

COLOR: Red

RECOAT TIME: 14-16 hours

COVERAGE: 1-1,5 m²/l

SIZE: 4-15 l

waterproof paint



*white
with fiber*

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 550% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Greater tensile strength by the incorporation of fiber.
Tensile strength of 35 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 4-8 hours

COLOR: White

RECOAT TIME: 14-16 hours

COVERAGE: 1-1,5 m²/l

SIZE: 4-15 l

waterproof paint



**grey
with fiber**

DESCRIPTION

Waterproof non-asphalt satin paint based on acrylic copolymers in emulsion. Once dry it forms a genuine rubber film, completely waterproof. Ideal for waterproofing terraces, rooftops, roofs, etc.

FEATURES

Completely waterproof.
Breathable.
The film formed is permeable to air and water vapour, allowing for breathing support.
Extraordinary elasticity, greater than 550% elongation.
Neither cracks nor fissures with movement.
Resistance to aging, to weathering and UV rays.
Excellent adhesion to all types of construction materials, such as concrete, brick, cement, fibre cement, metal, etc.
Greater tensile strength by the incorporation of fiber.
Tensile strength of 35 Kg/cm².
Its extreme adherence and penetration in cracks and pores as well as its elasticity make it perfect for supporting expansion and contraction without cracking or peeling.
Easy application.

FINISH: Satin

DRY TIME: 4-8 hours

COLOR: Grey

RECOAT TIME: 14-16 hours

COVERAGE: 1-1,5 m²/l

SIZE: 4-15 l

sports paint



tennis red

DESCRIPTION

Matte acrylic paint based high-resistance and light fast acrylic copolymers. Ideal for tennis courts and other sporting facilities.

FEATURES

- Great covering power.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Breathable.
- Completely waterproof.
- Weather-proof and UV-resistant.
- Stable color.
- Does not give off odours hazardous to health.
- Film thickness of 100-150 microns when wet and 35-50 microns when dry, depending on the type and condition of surface, absorption, mode of application and degree of paint dilution.
- Well-balanced color, covering and washability for protection of indoor and outdoor walls.
- Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: Tennis red

RECOAT TIME: 3 hours

COVERAGE: 6-8 m²/l

SIZE: 4-15 l

sports paint



tennis green

DESCRIPTION

Matte acrylic paint based high-resistance and light fast acrylic copolymers. Ideal for tennis courts and other sporting facilities.

FEATURES

- Great covering power.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Breathable.
- Completely waterproof.
- Weather-proof and UV-resistant.
- Stable color.
- Does not give off odours hazardous to health.
- Film thickness of 100-150 microns when wet and 35-50 microns when dry, depending on the type and condition of surface, absorption, mode of application and degree of paint dilution.
- Well-balanced color, covering and washability for protection of indoor and outdoor walls.
- Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: Tennis green

RECOAT TIME: 3 hours

COVERAGE: 6-8 m²/l

SIZE: 4-15 l

sports paint



tennis white

DESCRIPTION

Matte acrylic paint based high-resistance and light fast acrylic copolymers. Ideal for tennis courts and other sporting facilities.

FEATURES

- Great covering power.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Breathable.
- Completely waterproof.
- Weather-proof and UV-resistant.
- Stable white, not yellow.
- Does not give off odours hazardous to health.
- Film thickness of 100-150 microns when wet and 35-50 microns when dry, depending on the type and condition of surface, absorption, mode of application and degree of paint dilution.
- Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.
- Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: Tennis white

RECOAT TIME: 3 hours

COVERAGE: 6-8 m²/l

SIZE: 4-15 l

sports paint



tennis blue

DESCRIPTION

Matte acrylic paint based high-resistance and light fast acrylic copolymers. Ideal for tennis courts and other sporting facilities.

FEATURES

- Great covering power.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Breathable.
- Completely waterproof.
- Weather-proof and UV-resistant.
- Stable color.
- Does not give off odours hazardous to health.
- Film thickness of 100-150 microns when wet and 35-50 microns when dry, depending on the type and condition of surface, absorption, mode of application and degree of paint dilution.
- Well-balanced color, covering and washability for protection of indoor and outdoor walls.
- Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: Tennis blue

RECOAT TIME: 3 hours

COVERAGE: 6-8 m²/l

SIZE: 4-15 l

sports paint



fronton green

DESCRIPTION

Matte acrylic paint based high-resistance and light fast acrylic copolymers. Ideal for tennis courts and other sporting facilities.

FEATURES

- Great covering power.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Breathable.
- Completely waterproof.
- Weather-proof and UV-resistant.
- Stable color.
- Does not give off odours hazardous to health.
- Film thickness of 100-150 microns when wet and 35-50 microns when dry, depending on the type and condition of surface, absorption, mode of application and degree of paint dilution.
- Well-balanced color, covering and washability for protection of indoor and outdoor walls.
- Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: Fronton green

RECOAT TIME: 3 hours

COVERAGE: 6-8 m²/l

SIZE: 4-15 l

sports paint



pools

DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion with highly-resistant pigments and light fastness. Ideal for painting pools.

FEATURES

- Great covering power.
- Excellent adhesion on cement and concrete.
- Breathable.
- Completely waterproof.
- Completely resistant to pool purification agents.
- Alkali-resistant for brackets.
- Fast drying with bactericide and algacide action.
- Easy application.

FINISH: Matte

DRY TIME: 30 minutes

COLOR: Blue

RECOAT TIME: 2-4 hours

COVERAGE: 6-8 m²/l

SIZE: 4-15 l

Pimasa

www.pimasapaints.com

Parque Empresarial Campollano, calle D, 43 · 02007 Albacete Spain · T +34 967 218 528 · info@pinturaspimasa.com