

TECHNICAL DATASHEET

Printing date: 30/03/2017

Revision date: 30/03/2017

SECTION 1.- DESCRIPTION

High-quality satin acrylic paint based on copolymer resins in watery dispersion and high-resistance and stable pigments that provide waterproof, durable, washable and opaque finishes. It offers a nice decorative look with satin effect. Ideal for decoration and protection of both interior and exterior surfaces.

SECTION 2.- CHARACTERISTICS

- Very good covering power.
- Weather-proof and UV-resistant.
- Forms a mould-resistant film.
- Stable white, not yellow.
- Resistance to wet scrub over 10,000 cycles.
- Well-balanced whiteness, covering and washability, with adequate time for retouching.
- Excellent washability.
- Easy application.

SECTION 3.- TECHNICAL SPECIFICATIONS

Colour	White
Aspect	Liquid unctuous
Film aspect	Satin.
Odour	Characteristic
Solvent	Water
Density	1.34 gr/cm ³ approx.
Drying time (minimum)	30 minutes
Coverage	9-13 m ² /L according to surface conditions and absorption
Second coat waiting time (minimum)	2-4 hours (20° C and 65% relative humidity)
Washability	Excellent.
Resistance to wet scrub	Over 10.000 cycles (UNE 48243)
Viscosity	52% ±2% weight
Cleaning tools	Water

SECTION 4.- ATTRIBUTES

This paint has a well-balanced whiteness, and is easy to use. Excellent washability and very good covering power for interior and exterior surfaces. It is possible to obtain any colour mixing with a watery concentrated



SATIN 1000 MUX

colourant and apply on coarse surfaces.

SECTION 5.- APPLICATION

Available to use with brush, roller or spray gun. The surfaces must be prepared, firm, dry and cleaned in order to get free of dust, dirt, oil, grease, wax, chalk.

All surfaces with old paintings must be scraped and fully cleaned. When old paints are well fixed and it is not possible to scrap, apply a coat of fixer.

SECTION 6.- ADVICE

Avoid any extreme conditions. Do not apply under 5º C, before night hours, rainy days or on wet surfaces to obtain an adequate coat film.

SECTION 7.- SIZES

Containers available for 4 L and 15 L.

SECTION 8.- STORAGE

Original, unopened containers may be stored up to 12 months. Preserve from direct sun exposure as well as from freezing.

SECTION 9.- REMARKS

The information in this Technical Datasheet is the result of Pimasa's knowledge, based on laboratory testing and practical experience. Pinturas Pimasa reserves the right to modify the data provided without prior notice. If there is any inconsistency between different language issues in this document, the Spanish version shall prevail.