



TECHNICAL DATASHEET

Printing date: 30/03/2017

Revision date: 30/03/2017

SECTION 1.- DESCRIPTION

This is a versatile product developed to protect any type of surface for a long time. Smooth matte coating based on high-strength acrylic resins with weather-proof and light fast ingredients. If it is applying on cement or gypsum, it is recommended to apply Decotex, at least, four weeks later. Ideal for decoration and protection in all types of facades and other construction materials. Suitable for interior and exterior surfaces.

SECTION 2.- CHARACTERISTICS

- Excellent covering power.
- Colours availables according chart.
- Maximum whiteness.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Stable white, does not go yellow.
- Forms a highly mould-resistant film.
- Completely waterproof and UV-resistant
- Sufficiently permeable to water vapour to prevent internal condensation
- Not self-ignitable
- Breathable
- Self-cleaning.
- Easy application.

SECTION 3.- TECHNICAL SPECIFICATIONS

Colour	Colour chart available
Aspect	Liquid unctuous
Film aspect	Matte
Odour	Characteristic
Solvent	Water
Density	1.45-1.50 gr/cm ³ aprox.
Drying time (minimum)	30 minutes
Coverage	10-12 m ² /L according to surface conditions and absorption
Second coat waiting time (minimum)	2 hours (20° C and 65% relative humidity)
Washability	Excellent.
Resistance to wet scrub	Over 10.000 cycles (UNE 48243)
Drying total hardness	7 days
Viscosity	61% ±2% weight. According to colours

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product.
www.pinturaspimasa.com



DECOTEX COLOURS SMOOTH COATING

Cleaning tools

Water

SECTION 4.- ATTRIBUTES

This product has been developed to apply at any surface (interior or exterior) due completely smooth finish. It has got an excellent effectiveness against mould and is easy to use. Its high capacity to be permeable avoids internal condensation. This product is self-cleaning (by rain or hosing down). It is highly resistant to alkaline products.

SECTION 5.- APPLICATION

Available to use with brush or roller. The surfaces must be prepared, firm, dry and cleaned in order to get free of dust, dirt, oil, grease, wax, chalk. All surfaces with old paintings must be scraped and fully cleaned. When old paints are well fixed and it is not possible to scrap, apply a coat of fixer and two coats of Decotex. First coating must be dissolute with 10% water and second coat with 5%.

SECTION 6.- ADVICE

Avoid any extreme conditions. Do not apply under 5° C, before night hours, rainy days or on wet surfaces to obtain an adequate coat film. Otherwise it will not be possible to get a perfect film.

SECTION 7.- SIZES

Containers available for 4 L and 15 L.

SECTION 8.- STORAGE

Original, unopened containers may be stored up to 12 months. Preserve from direct sun exposure as well as from freezing.

SECTION 9.- REMARKS

The information in this Technical Datasheet is the result of Pimasa's knowledge, based on laboratory testing and practical experience. Pinturas Pimasa reserves the right to modify the data provided without prior notice. If there is any inconsistency between different language issues in this document, the Spanish version shall prevail.