

# Pimasa



## DECOTEX WHITE COATING

### TECHNICAL DATASHEET

Printing date: 05/05/2020

Revision date: 30/03/2017

#### SECTION 1.- DESCRIPTION

This is a versatile product developed to protect any type of surface for a long time. Smooth matte coating based on high-strength acrylic resins with weather-proof and light fast ingredients. Ideal for decoration and long-term protection for all kinds of facades. If it is applying on cement or gypsum, it is recommended to apply Decotex, at least, four weeks later. Ideal for decoration and protection in all types of facades and other construction materials. Suitable for interior and exterior surfaces.

#### SECTION 2.- CHARACTERISTICS

- Excellent covering power.
- Maximum whiteness.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Stable white, does not go yellow.
- Forms a highly mould-resistant film.
- Completely waterproof and UV-resistant
- Sufficiently permeable to water vapour to prevent internal condensation
- Not self-ignitable
- Breathable
- Self-cleaning.
- Easy application.

#### SECTION 3.- TECHNICAL SPECIFICATIONS

<b>Colour</b>	Colour chart available
<b>Aspect</b>	Liquid unctuous
<b>Film aspect</b>	Matte
<b>Odour</b>	Characteristic
<b>Solvent</b>	Water
<b>Density</b>	1.54 gr/cm <sup>3</sup> approx.
<b>Drying time (minimum)</b>	30 minutes
<b>Coverage</b>	9-132 m <sup>2</sup> /L according to surface conditions and absorption
<b>Second coat waiting time (minimum)</b>	2 hours (20° C and 65% relative humidity)

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product.  
[www.pinturaspimasa.com](http://www.pinturaspimasa.com)

# Pimasa



## DECOTEX WHITE COATING

<b>Washability</b>	Excellent.
<b>Resistance to wet scrub</b>	Over 10.000 cycles (UNE 48243)
<b>Drying total hardness</b>	7 days
<b>Viscosity</b>	63% $\pm$ 2% weight.
<b>Cleaning tools</b>	Water

### SECTION 4.- ATTRIBUTES

This product has been developed to apply at any surface (interior or exterior) due completely smooth finish. It has got an excellent effectiveness against mould and is easy to use. Its high capacity to be permeable avoids internal condensation. This product is self-cleaning (by rain or hosing down). It is highly resistant to alkaline products.

### SECTION 5.- APPLICATION

Available to use with brush or roller. The surfaces must be prepared, firm, dry and cleaned in order to get free of dust, dirt, oil, grease, wax, chalk. All surfaces with old paintings must be scraped and fully cleaned. When old paints are well fixed and it is not possible to scrap, apply a coat of fixer and two coats of Decotex. First coating must be dissolve with 10% water and second coat with 5%.

### SECTION 6.- ADVICE

Avoid any extreme conditions. Do not apply under 5° C, before night hours, rainy days or on wet surfaces to obtain an adequate coat film. Otherwise it will not be possible to get a perfect film.

### SECTION 7.- SIZES

Containers available for 4 L and 15 L.

### SECTION 8.- STORAGE

Original, unopened containers may be stored up to 12 months. Preserve from direct sun exposure as well as from freezing.

### SECTION 9.- REMARKS

The information in this Technical Datasheet is the result of Pimasa's knowledge, based on laboratory testing and practical experience. Pinturas Pimasa reserves the right to modify the data provided without prior notice. If there is any inconsistency between different language issues in this document, the Spanish version shall

# Pimasa



**DECOTEX WHITE COATING**

prevail.

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product.  
[www.pinturaspimasa.com](http://www.pinturaspimasa.com)