

# Pimasa



## INTERIOR MATTE 2001

### TECHNICAL DATASHEET

Printing date: 04/05/2020

Revision date: 25/01/2017

#### SECTION 1.- DESCRIPTION

Matte acrylic paint based on acrylic resins in a watery dispersion and highly resistant light-fastness pigments. Ideal for decoration and protection of interior surfaces.

#### SECTION 2.- CHARACTERISTICS

- Excellent adhesion on cement, concrete, brick and other construction materials.
- Stable white, not yellow.
- Well-balanced whiteness, for protection of indoor walls.
- Easy application.
- Not self-ignitable
- Fireproof
- Breathable

#### SECTION 3.- TECHNICAL SPECIFICATIONS

<b>Colour</b>	White
<b>Aspect</b>	Liquid
<b>Film aspect</b>	Matte
<b>Odour</b>	Characteristic
<b>Solvent</b>	Water
<b>Density</b>	1.55 gr/cm <sup>3</sup> aprox.
<b>Drying time (minimum)</b>	30 minutes
<b>Coverage</b>	6-12 m <sup>2</sup> /L. according to surface conditions and absorption
<b>Second coat waiting time (minimum)</b>	2 – 4 hours (20° C and 65% relative humidity)
<b>Viscosity</b>	66% ±2% weight
<b>Cleaning tools</b>	Water

#### SECTION 4.- ATTRIBUTES

This paint has a well-balanced whiteness, and is easy to use.

#### SECTION 5.- APPLICATION

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product.  
[www.pinturaspimasa.com](http://www.pinturaspimasa.com)

# Pimasa



## INTERIOR MATTE 2001

Suitable for decoration and protection of interior surfaces such as concrete, gypsum, plaster and heat-resistant materials.

### SECTION 6.- ADVICE

Available to use with brush, roller or spray gun. The surfaces must be prepared, firm, dry and cleaned in order to get free of dust, dirt, oil, grease, wax, chalk. All surfaces with old paintings must be scraped and fully cleaned. When old paints are well fixed and it is not possible to scrap, apply a coat of fixer. Do not apply under 5° C.

### SECTION 7.- SIZES

Containers available for 4 L and 15 L.

### SECTION 8.- STORAGE

Original, unopened containers may be stored up to 12 months. Preserve from direct sun exposure as well as from freezing.

### SECTION 9.- REMARKS

The information in this Technical Datasheet is the result of Pimasa's knowledge, based on laboratory testing and practical experience. Pinturas Pimasa reserves the right to modify the data provided without prior notice. If there is any inconsistency between different language issues in this document, the Spanish version shall prevail.