

Pimasa



R-520

TECHNICAL DATASHEET

Printing date: 04/05/2020

Revision date: 30/03/2017

SECTION 1.- DESCRIPTION

Matte coating based on acrylic copolymers in emulsion resins in a watery dispersion and highly resistant light-fast ingredients.
Ideal for decoration and protection for interior and exterior, used by professional painters.

SECTION 2.- CHARACTERISTICS

- Good covering power.
- Maximum whiteness.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Breathable.
- Completely waterproof and UV-resistant.
- Stable white, not yellow.
- Well-balanced whiteness, covering and washability for protection of indoor and outdoor walls.
- Excellent washability.
- Easy application.

SECTION 3.- TECHNICAL SPECIFICATIONS

Colour	White
Aspect	Liquid unctuous
Film aspect	Matte
Odour	Characteristic
Solvent	Water
Density	1.55 gr/cm ³ aprox.
Drying time (minimum)	30 minutes
Coverage	9-13 m ² /L
Second coat waiting time (minimum)	2-4 hours (20° C and 65% relative humidity)
Washability	Optimal
Viscosity	63% ±2% weight
Cleaning tools	Water

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product.
www.pinturaspimasa.com

Pimasa



R-520

SECTION 4.- ATTRIBUTES

The composition of this product provides long-term resistance to environmental variability in the different surfaces to coat (interior and exterior). This paint has a well-balanced whiteness and high covering power. It is easy to use. Optimal washability and It is highly resistant to alkaline products and abrasion.

SECTION 5.- APPLICATION

Suitable for decoration and protection of interior and exterior surfaces such as concrete, gypsum, plaster and heat-resistant materials.

SECTION 6.- ADVICE

Available to use with brush, roller or spray gun. The surfaces must be prepared, firm, dry and cleaned in order to get free of dust, dirt, oil, grease, wax, chalk. All surfaces with old paintings must be scraped and fully cleaned. When old paints are well fixed and it is not possible to scrap, apply a coat of fixer. Do not apply under 5° C.

SECTION 7.- SIZES

Containers available for 4 L and 15 L.

SECTION 8.- STORAGE

Original, unopened containers may be stored up to 12 months. Preserve from direct sun exposure as well as from freezing.

SECTION 9.- REMARKS

The information in this Technical Datasheet is the result of Pimasa's knowledge, based on laboratory testing and practical experience. Pinturas Pimasa reserves the right to modify the data provided without prior notice. If there is any inconsistency between different language issues in this document, the Spanish version shall prevail.