

# Pimasa



## SATIN EXTRA

### TECHNICAL DATASHEET

Printing date: 05/05/2020

Revision date: 30/03/2017

#### SECTION 1.- DESCRIPTION

High-quality satin acrylic paint based on copolymer resins in watery dispersion and high-resistance and stable pigments that provide waterproof, durable, washable and opaque finishes. It offers a nice decorative look with satin effect. Ideal for decoration and protection of both interior and exterior surfaces.

#### SECTION 2.- CHARACTERISTICS

- High-gloss acrylic paint.
- Excellent covering power.
- Completely waterproof.
- Weather-proof and UV-resistant.
- Forms a mould-resistant film.
- Stable white, not yellow.
- Resistance to wet scrub over 10,000 cycles.
- Well-balanced whiteness, covering and washability, with adequate time for retouching.
- Excellent washability.
- Easy application.

#### SECTION 3.- TECHNICAL SPECIFICATIONS

<b>Colour</b>	White
<b>Aspect</b>	Liquid unctuous
<b>Film aspect</b>	Satin.
<b>Odour</b>	Characteristic
<b>Solvent</b>	Water
<b>Density</b>	1.32 gr/cm <sup>3</sup> approx.
<b>Drying time (minimum)</b>	30 minutes
<b>Coverage</b>	9-13 m <sup>2</sup> /L according to surface conditions and absorption
<b>Second coat waiting time (minimum)</b>	2-4 hours (20° C and 65% relative humidity)
<b>Washability</b>	Excellent.
<b>Resistance to wet scrub</b>	Over 10.000 cycles (UNE 48243)
<b>Viscosity</b>	53% ±2% weight
<b>Cleaning tools</b>	Water

The Technical Data Sheet (TDS) is recommended to be read in conjunction with the Safety Data Sheet (SDS) for this product. [www.pinturaspimasa.com](http://www.pinturaspimasa.com)

# Pimasa



## SATIN EXTRA

### SECTION 4.- ATTRIBUTES

This paint has a well-balanced whiteness, and is easy to use. Excellent washability and very good covering power for interior and exterior surfaces. It is possible to obtain any colour mixing with a watery concentrated colourant and apply on coarse surfaces.

### SECTION 5.- APPLICATION

Available to use with brush, roller or spray gun. The surfaces must be prepared, firm, dry and cleaned in order to get free of dust, dirt, oil, grease, wax, chalk.  
All surfaces with old paintings must be scraped and fully cleaned. When old paints are well fixed and it is not possible to scrap, apply a coat of fixer.

### SECTION 6.- ADVICE

Avoid any extreme conditions. Do not apply under 5º C, before night hours, rainy days or on wet surfaces to obtain an adequate coat film.

### SECTION 7.- SIZES

Containers available for 4 L and 15 L.

### SECTION 8.- STORAGE

Original, unopened containers may be stored up to 12 months. Preserve from direct sun exposure as well as from freezing.

### SECTION 9.- REMARKS

The information in this Technical Datasheet is the result of Pimasa's knowledge, based on laboratory testing and practical experience. Pinturas Pimasa reserves the right to modify the data provided without prior notice. If there is any inconsistency between different language issues in this document, the Spanish version shall prevail.