

Pimasa



TENNIS BLUE

TECHNICAL DATASHEET

Printing date: 05/05/2020

Revision date: 30/03/2016

SECTION 1.- DESCRIPTION

Matte acrylic paint based on high-resistance and light fast acrylic copolymers. Ideal for tennis courts and other sports facilities.

SECTION 2.- CHARACTERISTICS

- Great covering power.
- Excellent adhesion on cement, concrete, brick and other construction materials.
- Does not give off odours hazardous to health.
- Breathable.
- Non combustible
- Completely waterproof.
- Weather-proof and UV-resistant.

SECTION 3.- TECHNICAL SPECIFICATIONS

Colour	Blue
Aspect	Liquid.
Film aspect	Matte.
Odour	Characteristic.
Solvent	Water.
Density	1.352 to 1.405 gr./cm ³ .
Drying time (minimum)	30 minutes
Coverage	6-8 m ² /L according to surface conditions and absorption
Second coat waiting time (minimum)	From 3 hours (20° C and 65% relative humidity)
Total drying time (minimun)	10 days, depending on the ambient temperature
Washability	Excellent.
Film thickness	100-150 microns when wet and 35-50 microns when dry, depending on the type and condition of surface, absorption, mode of application and degree of paint dilution.
Cleaning tools	Water.

Pimasa



TENNIS BLUE

SECTION 4.- ATTRIBUTES

Well-balanced colour, covering and washability for protection of indoor and outdoor. It is highly resistant to alkaline products and abrasion. Easy application.

SECTION 5.- APPLICATION

All surfaces must be prepared, firm, dry and cleaned in order to get free of dust, dirt, oil, grease, wax, chalk, mould or any other contamination or condition that could adversely affect the performance of the coating. Cement, it must be thoroughly cured before painting. In order to get the highest efficiency, the first coating must be applied with dissolution of 15% of water and the second coating with 5% water dissolution. If surface to paint was painted before use and in good condition, it must be clean. If surface to paint is in no good condition, cracked or chipped off, it will be necessary to prepare it them before use.

SECTION 6.- ADVICE

Available to use with brush, roller or spray gun. It is very important to homogenize the product before to be used. Avoid any extreme conditions. Do not apply under 5° C, before night hours, rainy days or on wet surfaces to obtain an adequate coat film.

SECTION 7.- SIZES

Containers available for 4 L and 15 L.

SECTION 8.- STORAGE

Original, unopened containers may be stored up to 12 months. Preserve from direct sun exposure as well as from freezing.

SECTION 9.- REMARKS

The information in this Technical Datasheet is the result of Pimasa's knowledge, based on laboratory testing and practical experience. Pinturas Pimasa reserves the right to modify the data provided without prior notice. If there is any inconsistency between different language issues in this document, the Spanish version shall prevail.